


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 70.78 lm/W
MODEL	BL07-30W-930-W-60	Imax(cd)	2005	S/MH(C0/180)	0.77	
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	0.74	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	2095.0	η UP,DN(C0-180)	1.3,48.4	
NOMINAL FLUX(lm)	2095.04	CIE CLASS	DIRECT	η UP,DN(C180-360)	1.4,48.9	
LAMPS INSIDE	1	η up(%)	2.7	CIBSE SHR NOM	0.75	
TEST VOLTAGE(V)	226.6	η down(%)	97.3	CIBSE SHR MAX	0.90	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:QiuMing
 Test Date:2015-10-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
 Humidity:65.0%
 Test Distance:5.920m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1765	1750	1713	1710	1727	1754	1788	1786	0- 10	178.6	178.6	8.52,8.52
20	1263	1245	1220	1214	1239	1272	1310	1295	10- 20	417.9	596.5	28.5,28.5
30	1295	1301	1297	1295	1250	1209	1323	1305	20- 30	573.8	1170	55.9,55.9
40	666.7	655.2	652.1	652.7	649.0	643.4	664.5	659.6	30- 40	532.7	1703	81.3,81.3
50	55.78	50.96	47.57	48.72	50.00	52.24	49.99	49.23	40- 50	279.4	1982	94.6,94.6
60	23.30	23.14	22.63	22.40	22.31	21.19	21.98	22.58	50- 60	31.22	2014	96.1,96.1
70	7.643	8.399	8.149	7.647	6.868	6.096	6.396	6.937	60- 70	14.03	2028	96.8,96.8
80	5.182	5.380	5.448	5.264	5.050	4.743	4.744	4.980	70- 80	5.685	2033	97.1,97.1
90	4.382	5.143	4.508	3.761	4.008	4.055	4.027	4.021	80- 90	5.568	2039	97.3,97.3
100	4.584	4.594	4.576	4.680	5.180	5.094	5.011	4.981	90-100	4.687	2044	97.5,97.5
110	6.070	6.272	6.188	6.297	6.848	6.537	6.369	6.352	100-110	5.921	2049	97.8,97.8
120	7.758	7.921	7.735	7.900	8.505	8.243	7.956	7.988	110-120	7.096	2057	98.2,98.2
130	9.916	9.966	9.675	9.871	10.59	10.37	9.952	10.04	120-130	8.041	2065	98.5,98.5
140	12.42	12.22	11.73	12.03	12.76	12.74	12.26	12.35	130-140	8.625	2073	99.99
150	14.64	14.03	13.51	13.74	14.48	15.04	14.83	14.75	140-150	8.398	2082	99.4,99.4
160	16.10	15.31	14.79	15.00	15.79	16.56	16.78	16.67	150-160	6.978	2089	99.7,99.7
170	17.71	16.75	16.30	16.85	17.69	18.59	19.29	18.93	160-170	4.736	2093	99.9,99.9
180	16.95	17.17	17.55	17.99	16.99	17.14	17.56	17.97	170-180	1.693	2095	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

WEC AND CCEC

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

pcc	80%	70%	50%	30%	10%	0
pw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
pfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Wall Exitance Coefficients(WEC)
0.0						
1.0	.197 .112 .035	.189 .108 .034	.175 .100 .032	.162 .093 .030	.150 .087 .028	
2.0	.189 .104 .032	.183 .101 .031	.170 .095 .029	.159 .089 .028	.149 .084 .027	
3.0	.181 .096 .029	.175 .094 .028	.164 .089 .027	.155 .085 .026	.146 .081 .025	
4.0	.172 .089 .026	.167 .087 .026	.158 .084 .025	.149 .080 .024	.141 .077 .023	
5.0	.164 .084 .024	.160 .082 .024	.151 .079 .023	.144 .076 .023	.137 .073 .022	
6.0	.156 .078 .022	.152 .077 .022	.145 .074 .022	.138 .072 .021	.132 .069 .021	
7.0	.149 .074 .021	.146 .073 .021	.139 .070 .020	.133 .068 .020	.127 .066 .019	
8.0	.142 .070 .020	.139 .069 .019	.133 .067 .019	.128 .065 .019	.122 .063 .018	
9.0	.136 .066 .018	.133 .065 .018	.128 .063 .018	.123 .062 .018	.118 .060 .017	
10.0	.130 .062 .017	.128 .062 .017	.123 .060 .017	.118 .059 .017	.114 .057 .016	

pcc	80%	70%	50%	30%	10%	0
pw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
pfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio					Ceiling Cavity Exitance Coefficients(CCEC)
0.0	.211 .211 .211	.180 .180 .180	.123 .123 .123	.071 .071 .071	.023 .023 .023	
1.0	.193 .178 .164	.165 .153 .141	.113 .105 .098	.065 .061 .057	.021 .020 .018	
2.0	.179 .153 .131	.154 .132 .113	.105 .091 .079	.061 .053 .046	.019 .017 .015	
3.0	.168 .135 .108	.144 .116 .093	.099 .081 .066	.057 .047 .039	.018 .015 .013	
4.0	.159 .120 .091	.136 .104 .079	.094 .072 .056	.054 .042 .033	.017 .014 .011	
5.0	.151 .109 .078	.130 .094 .068	.089 .066 .048	.052 .039 .028	.017 .013 .009	
6.0	.144 .100 .068	.124 .087 .060	.085 .061 .042	.050 .036 .025	.016 .012 .008	
7.0	.138 .093 .061	.119 .080 .053	.082 .056 .038	.048 .033 .022	.015 .011 .007	
8.0	.132 .087 .055	.114 .075 .048	.079 .053 .034	.046 .031 .020	.015 .010 .007	
9.0	.127 .082 .051	.110 .071 .044	.076 .050 .032	.044 .029 .019	.014 .010 .006	
10.0	.123 .077 .047	.106 .067 .041	.073 .047 .029	.043 .028 .017	.014 .009 .006	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

Uncorrected UGR Table

NAME:					TYPE:			WEIGHT:			
DIM.:					SPEC.:			SERIAL No.:			
MFR.: Rayconn					SUR.:			PROTECTION ANGLE:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	20.8	21.9	21.1	22.1	22.3	20.7	21.7	21.0	22.0	22.2
	3H	20.6	21.6	20.9	21.8	22.1	20.5	21.5	20.8	21.7	22.0
	4H	20.6	21.4	20.9	21.7	22.0	20.4	21.3	20.8	21.6	21.9
	6H	20.5	21.3	20.8	21.6	21.9	20.4	21.2	20.7	21.5	21.8
	8H	20.4	21.2	20.8	21.5	21.9	20.3	21.1	20.7	21.4	21.8
	12H	20.4	21.2	20.8	21.5	21.8	20.3	21.1	20.7	21.4	21.7
4H	2H	20.5	21.4	20.9	21.7	22.0	20.4	21.3	20.8	21.6	21.9
	3H	20.4	21.1	20.7	21.5	21.8	20.3	21.0	20.6	21.4	21.7
	4H	20.3	21.0	20.7	21.3	21.7	20.2	20.9	20.6	21.2	21.6
	6H	20.2	20.8	20.6	21.2	21.6	20.1	20.7	20.5	21.1	21.5
	8H	20.2	20.7	20.6	21.1	21.6	20.1	20.6	20.5	21.0	21.5
	12H	20.2	20.7	20.6	21.1	21.5	20.1	20.6	20.5	21.0	21.5
8H	4H	20.1	20.7	20.6	21.1	21.5	20.0	20.6	20.5	21.0	21.4
	6H	20.1	20.5	20.5	21.0	21.5	20.0	20.4	20.4	20.9	21.3
	8H	20.1	20.5	20.6	20.9	21.4	20.0	20.4	20.5	20.8	21.3
	12H	20.1	20.4	20.6	20.9	21.4	20.0	20.3	20.5	20.8	21.3
12H	4H	20.1	20.6	20.5	21.0	21.5	20.0	20.5	20.4	20.9	21.4
	6H	20.0	20.4	20.5	20.9	21.4	19.9	20.3	20.4	20.8	21.3
	8H	20.0	20.4	20.5	20.9	21.4	19.9	20.3	20.4	20.8	21.3
Variations with the observer position at spacings:											
S = 1.0H		+ 3.0 / - 9.4					+ 3.0 / - 9.3				
1.5H		+ 3.4 / - 9.7					+ 3.5 / - 9.3				
2.0H		+ 8.0 / - 6.5					+ 7.9 / - 5.9				

CIE Pub.117 Corrected 2095 lm Total Lamp Luminous Flux.(8log(F/F0) = 2.6)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	80	72	68	79	72	68	78	72	67	63
0.80	88	81	77	87	81	77	86	80	76	72
1.00	94	87	83	93	87	83	91	87	82	77
1.25	99	93	89	98	92	88	95	91	87	82
1.50	102	96	92	101	96	92	98	94	91	85
2.00	106	101	97	104	100	96	101	97	94	88
2.50	108	103	100	106	102	99	102	99	96	90
3.00	109	106	102	107	104	101	104	101	98	91
4.00	112	108	106	109	107	104	105	103	101	93
5.00	113	110	108	111	108	106	106	104	103	94
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 γ Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:




C Range: 0 - 360DEG	γ Range: 0 - 180DEG
C Interval: 15.0DEG	γ Interval: 1.0DEG
Test Speed: HIGH	Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Temperature: 25.3DEG	Humidity: 65.0%
Operators: QiuMing	Test Distance: 5.920m [K=1.0000]
Test Date: 2015-10-27	Remarks:

AAI Figure

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

Flux out:1360 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270
0	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001	2001
5	1948	1950	1940	1941	1933	1931	1919	1918	1909	1911	1907	1912	1915	1914	1923	1924	1935	1935	1946
10	1765	1766	1750	1750	1732	1728	1713	1714	1704	1710	1707	1717	1727	1728	1750	1754	1774	1774	1788
15	1509	1512	1496	1492	1471	1471	1454	1460	1449	1456	1450	1464	1479	1482	1509	1512	1535	1536	1557
20	1263	1270	1253	1245	1231	1231	1220	1222	1209	1214	1213	1224	1239	1248	1274	1272	1290	1293	1310
25	1232	1214	1165	1115	1126	1131	1126	1120	1126	1135	1169	1191	1211	1249	1244	1258	1253	1260	1254
30	1295	1336	1330	1301	1268	1285	1297	1295	1284	1295	1265	1270	1250	1218	1193	1209	1255	1257	1323
35	803	810	802	809	791	800	794	792	783	794	778	782	775	766	763	751	779	793	800
40	667	668	662	655	633	655	652	649	642	653	646	649	649	639	651	643	652	657	664
45	455	492	451	481	422	464	417	428	395	403	373	385	383	358	384	370	397	389	420
50	55.8	56.9	52.3	51.0	49.4	49.4	47.6	47.7	47.7	48.7	48.7	49.8	50.0	49.9	51.0	52.2	53.2	51.0	50.0
55	35.1	34.8	33.8	33.8	33.3	34.1	33.4	33.7	33.6	34.8	35.0	36.5	36.2	34.7	34.3	33.5	33.7	33.1	33.7
60	23.3	23.4	22.9	23.1	22.6	22.9	22.6	22.6	22.1	22.4	22.1	22.4	22.3	21.5	21.5	21.2	21.6	21.4	22.0
65	14.6	15.0	14.8	15.1	14.8	14.9	14.6	14.7	14.3	14.4	13.9	13.9	13.7	13.0	13.0	12.6	12.9	12.7	13.1
70	7.64	8.05	8.10	8.40	8.32	8.52	8.15	8.17	7.71	7.65	7.19	7.11	6.87	6.38	6.38	6.10	6.26	6.11	6.40
75	5.27	5.36	5.41	5.46	5.50	5.52	5.53	5.49	5.43	5.35	5.24	5.10	5.06	4.93	4.81	4.73	4.67	4.69	4.73
80	5.18	5.27	5.33	5.38	5.42	5.44	5.45	5.40	5.35	5.26	5.17	5.04	5.05	4.93	4.81	4.74	4.69	4.71	4.74
85	5.18	5.25	5.33	5.37	5.41	5.43	5.44	5.41	5.37	5.28	5.18	5.06	5.14	5.03	4.91	4.85	4.80	4.81	4.85
90	4.38	4.95	4.82	5.14	4.91	5.13	4.51	4.62	3.80	3.76	3.70	3.69	4.01	4.04	4.03	4.05	4.04	4.06	4.03
95	4.05	4.03	4.04	4.01	4.02	4.00	4.02	4.02	4.04	4.04	4.08	4.08	4.49	4.51	4.49	4.51	4.48	4.49	4.47
100	4.58	4.59	4.63	4.59	4.62	4.58	4.58	4.59	4.62	4.68	4.75	4.73	5.18	5.18	5.11	5.09	5.03	5.05	5.01
105	5.34	5.41	5.48	5.46	5.48	5.40	5.40	5.40	5.46	5.52	5.60	5.58	6.04	6.01	5.90	5.78	5.69	5.70	5.66
110	6.07	6.20	6.27	6.27	6.27	6.18	6.19	6.20	6.25	6.30	6.40	6.38	6.85	6.80	6.67	6.54	6.43	6.41	6.37
115	6.86	6.98	7.06	7.05	7.06	6.93	6.92	6.93	6.98	7.06	7.18	7.16	7.62	7.57	7.44	7.34	7.23	7.18	7.12
120	7.76	7.85	7.93	7.92	7.92	7.78	7.73	7.71	7.79	7.90	8.05	8.04	8.50	8.46	8.33	8.24	8.09	8.04	7.96
125	8.76	8.84	8.90	8.88	8.87	8.71	8.64	8.59	8.69	8.83	9.00	9.02	9.51	9.46	9.35	9.25	9.06	9.01	8.90
130	9.92	9.98	10.0	9.97	9.93	9.76	9.68	9.62	9.72	9.87	10.1	10.1	10.6	10.6	10.5	10.4	10.1	10.1	9.95
135	11.2	11.2	11.2	11.1	11.0	10.8	10.7	10.7	10.8	10.9	11.2	11.3	11.7	11.7	11.6	11.5	11.2	11.2	11.1
140	12.4	12.4	12.4	12.2	12.1	11.9	11.7	11.8	11.9	12.0	12.3	12.4	12.8	12.8	12.8	12.7	12.4	12.3	12.3
145	13.6	13.6	13.5	13.3	13.1	12.9	12.8	12.7	12.9	13.0	13.3	13.5	13.7	13.9	13.9	13.9	13.8	13.6	13.6
150	14.6	14.5	14.3	14.0	13.8	13.6	13.5	13.5	13.6	13.7	14.0	14.2	14.5	14.7	14.9	15.0	15.1	15.0	14.8
155	15.4	15.2	14.9	14.6	14.4	14.2	14.1	14.1	14.2	14.3	14.6	14.8	15.1	15.3	15.5	15.8	15.9	15.9	15.7
160	16.1	15.9	15.6	15.3	15.1	14.9	14.8	14.8	14.9	15.0	15.3	15.5	15.8	16.1	16.3	16.6	16.7	16.8	16.8
165	17.0	16.7	16.4	16.1	15.8	15.7	15.6	15.7	15.8	15.9	16.2	16.6	16.7	17.0	17.2	17.5	17.7	17.9	17.9
170	17.7	17.3	17.0	16.8	16.5	16.3	16.3	16.4	16.6	16.9	17.2	17.6	17.7	17.9	18.3	18.6	18.9	19.1	19.3
175	17.4	17.1	16.8	16.6	16.5	16.5	16.5	16.6	16.8	17.0	17.2	17.4	17.1	17.4	17.8	18.1	18.5	18.7	18.9
180	16.9	17.0	17.0	17.2	17.3	17.5	17.6	17.7	17.8	18.0	18.1	18.1	17.0	16.9	17.0	17.1	17.3	17.4	17.6

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: QiuMing
Test Date: 2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity: 65.0%
Test Distance: 5.920m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME:	TYPE:	WEIGHT:
DIM.:	SPEC.:	SERIAL No.:
MFR.: Rayconn	SUR.:	PROTECTION ANGLE:

Table--2

UNIT: cd

C(DEG) γ (DEG)	285	300	315	330	345														
0	2001	2001	2001	2001	2001														
5	1943	1952	1950	1957	1951														
10	1786	1798	1786	1792	1776														
15	1552	1563	1541	1544	1520														
20	1304	1313	1295	1293	1267														
25	1241	1225	1234	1232	1217														
30	1314	1332	1305	1314	1287														
35	799	807	800	803	797														
40	664	666	660	658	660														
45	406	444	422	466	443														
50	49.0	49.3	49.2	50.7	52.3														
55	33.8	34.6	34.5	34.8	34.9														
60	22.1	22.8	22.6	23.3	23.0														
65	13.3	13.8	13.7	14.2	14.2														
70	6.58	7.00	6.94	7.36	7.46														
75	4.81	4.88	4.98	5.09	5.21														
80	4.82	4.89	4.98	5.07	5.18														
85	4.91	4.98	5.07	5.16	5.26														
90	4.04	4.00	4.02	4.41	4.38														
95	4.47	4.44	4.43	4.40	4.40														
100	5.02	4.98	4.98	4.94	4.95														
105	5.70	5.65	5.63	5.62	5.63														
110	6.41	6.37	6.35	6.37	6.39														
115	7.16	7.12	7.13	7.15	7.20														
120	7.97	7.94	7.99	8.03	8.09														
125	8.89	8.88	8.96	9.00	9.07														
130	9.93	9.94	10.0	10.1	10.2														
135	11.0	11.0	11.2	11.2	11.3														
140	12.3	12.3	12.4	12.3	12.6														
145	13.7	13.6	13.5	13.5	13.8														
150	14.9	14.8	14.8	14.8	14.8														
155	15.7	15.7	15.7	15.7	15.5														
160	16.8	16.7	16.7	16.5	16.3														
165	17.9	17.8	17.7	17.5	17.2														
170	19.3	19.1	18.9	18.7	18.3														
175	18.9	18.9	18.7	18.7	18.3														
180	17.7	17.8	18.0	18.1	18.1														

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:QiuMing
Test Date:2015-10-27

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:5.920m [K=1.0000]
Remarks: